

Heucojet ES- series is a finely dispersed high performance pigment preparation with sub micron particle size with narrow distribution, specially developed for solvent inkjet ink application.

| PRODUCT DESCRIPTION | |
|---------------------|-------------|
| Color Index | Pigment Mix |
| Chemical Type | NA |

| FULL TONE | REDUCTION |
|--|---|
|  |  |

| PHYSICAL DATA | |
|-------------------------|---------------|
| Appearance | Yellow Liquid |
| pH | 5.0 - 7.0 |
| Viscosity [cPs] | 70-300 |
| Pigment Content(%) | 15 |
| Binder Content (%) | 10.5 |
| Particle Size (D50, µm) | 0.25-0.55 |

| APPLICATION PROFILE | |
|----------------------|-------------|
| Solvent Base Systems | Recommended |
| UV Curing | - |

| FASTNESS PROPERTIES | | |
|---------------------|-----|--------------------|
| Alkali Fastness | - | DIN EN ISO 14469-4 |
| Light Fastness | 6-7 | DIN EN ISO 105-B01 |
| Acid Fastness | - | DIN EN ISO 12877-2 |

| STANDARD PACKAGING |
|---|
| 25kg Cans |
| Specific packaging available on request |

® = Registered trademark of Heubach Colour Pvt. Ltd. Our product specifications and application information are based on our current knowledge. They are non-binding and cannot be taken as a guarantee. The processing company must establish the suitability of individual products itself. As their use lies beyond our knowledge and control, we cannot accept any liability relating to the use of our products in particular applications. In addition to that, the legal rights of third parties must always be considered. The specification agreed between the customer and ourselves is the basis upon which our general sales and delivery conditions are set and is the deciding factor concerning any liabilities. Our standard specification is then valid if no specification has been agreed upon between the customer and us.